

BELKIN



OmniView® LCD Rack Consoles

Complete Control

Compact 1U LCD Rack Console with Dual-Rail Technology



Dual-Rail Features

- **Dual-Rail Design** – Keyboard/mouse operates independent of LCD display; provides ability to display critical information with rack door closed
- **Integrated KVM** – Available Belkin OmniView® PRO3 KVM switches; 8- or 16-port KVM solution with the same 1U of space; scalable to manage up to 256 systems
- **Physical Security** – Included keyed lock; prevents unauthorized access to critical systems
- **Wide Viewing Angle** – 115-degree monitor articulation provides superior viewing flexibility
- **Premium LCD** – High-quality TFT-LCD display provides high-resolution support for today's changing requirements
- **Universal Mounting** – Adjustable mounting rails accommodate most 19-inch EIA rack/depth configuration
- **2-Year Warranty** – Belkin's assurance | [Quality. Service. Value.](#)

*Belkin OmniView PRO3 KVM Switches are the best-selling analog KVM switch worldwide (NPD Channel Data)

Product Specifications

Part Number	F1DC101P-DR	F1DC108B-DR	F1DC116B-DR
Rail Type	Dual-Rail Technology	Dual-Rail Technology	Dual-Rail Technology
Material/Enclosure	Heavy-Duty Steel	Heavy-Duty Steel	Heavy-Duty Steel
Built-In KVM Switch	No	Yes	Yes
Weight	32.6 lbs. (14.8kg)	33.3 lbs. (15.1kg)	36.1 lbs. (16.4kg)
Dimensions	26.1 x 17.6 x 1.74 in. (673 x 448 x 44.1mm)	26.1 x 17.6 x 1.74 in. (673 x 448 x 44.1mm)	26.1 x 17.6 x 1.74 in. (673 x 448 x 44.1mm)
KVM Switch	N/A	8 Ports	16 Ports
Users	1	1	1
Keyboard Type	Laptop Style	Laptop Style	Laptop Style
Keyboard/Mouse Connection	PS/2	PS/2, USB	PS/2, USB
Operating Life of Keys	8 Million Cycles	8 Million Cycles	8 Million Cycles
Mouse Type	Touch Pad Style	Touch Pad Style	Touch Pad Style
Display Type	17" LCD Active-Matrix Color	17" LCD Active-Matrix Color	17" LCD Active-Matrix Color
Maximum Resolution	1280x1024	1280x1024	1280x1024
Power/Environment			
Power	Auto-Switching 100 to 240VAC 50 to 60Hz, 48-Watt	12V DC 6A Power Adapter Center-Pin-Positive Polarity	12V DC 6A Power Adapter Center-Pin-Positive Polarity
Operating Temperature	32° to 104° F (0° to 40° C)	32° to 104° F (0° to 40° C)	32° to 104° F (0° to 40° C)
Storage Temperature	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)
Humidity	0-80% RH, Non-Condensing	0-80% RH, Non-Condensing	0-80% RH, Non-Condensing

Note: Specifications are subject to change without notice.

Single-Rail LCD Rack Console with Integrated KVM

Available in 8 or 16 Ports



Single-Rail Features

- **Single-Rail Design** – Easy-to-use, space-saving design for maximizing efficiency at the server rack
- **Integrated KVM** – Available Belkin OmniView KVM PRO3 KVM Switches, 8- or 16-port KVM solution within the same 1U of space; scalable to manage up to 256 systems
- **Physical Security** – Included keyed lock; prevents unauthorized access to critical systems
- **Wide Viewing Angle** – 115-degree monitor articulation provides superior viewing flexibility
- **Premium LCD** – High-quality TFT-LCD display provides high-resolution support for today’s changing requirements
- **Universal Mounting** – Adjustable mounting rails accommodate most 19-inch EAI rack/depth configuration
- **2-Year Warranty** – Belkin’s assurance | [Quality. Service. Value.](#)

Part Number	F1DC101P-SR	F1DC102P-SR	F1DC108B-SR	F1DC116B-SR
Rail Type	Single-Rail Technology	Single-Rail Technology	Single-Rail Technology	Single-Rail Technology
Material/Enclosure	Heavy-Duty Steel	Heavy-Duty Steel	Heavy-Duty Steel	Heavy-Duty Steel
Built-In KVM Switch	No	No	Yes	Yes
Weight	26.9 lbs. (12.2kg)	34.7 lbs. (15.7kg)	33.0 lbs. (15.0kg)	34.1 lbs. (15.5kg)
Dimensions	19 x 21.7 x 1.70 in. (482.6 x 551.2 x 43.18mm)	19 x 23.6 x 1.70 in. (482.6 x 599.4 x 43.18mm)	19 x 23.5 x 1.75 in. (482.6 x 597 x 44.5mm)	19 x 23.5 x 1.75 in. (482.6 x 597 x 44.5mm)
KVM Switch	N/A	N/A	8 Ports	16 Ports
Users	1	1	1	1
Keyboard Type	Laptop Style	Laptop Style	Laptop Style	Laptop Style
Keyboard/Mouse Connection	PS/2	PS/2	PS/2, USB	PS/2, USB
Operating Life of Keys	8 Million Cycles	8 Million Cycles	8 Million Cycles	8 Million Cycles
Mouse Type	Touch Pad Style	Touch Pad Style	Touch Pad Style	Touch Pad Style
Display Type	17" LCD Active-Matrix Color	19" LCD Active-Matrix Color	17" LCD Active-Matrix Color	17" LCD Active-Matrix Color
Maximum Resolution	1280x1024	1280x1024	1280x1024	1280x1024
Power/Environment				
Power	Auto-Switching 100 to 240VAC 50 to 60Hz, 48-Watt	Auto-Switching 100 to 240VAC 50 to 60Hz, 48-Watt	12V DC 6A Power Adapter Center-Pin-Positive Polarity	12V DC 6A Power Adapter Center-Pin-Positive Polarity
Operating Temperature	32° to 104° F (0° to 40° C)	32° to 104° F (0° to 40° C)	32° to 104° F (0° to 40° C)	32° to 104° F (0° to 40° C)
Storage Temperature	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)	-4° to 140° F (-20° to 60° C)
Humidity	0-80% RH, Non-Condensing	0-80% RH, Non-Condensing	0-80% RH, Non-Condensing	0-80% RH, Non-Condensing

Package Contents

SINGLE-/DUAL-RAIL LCD CONSOLE WITHOUT INTEGRATED KVM

- Rack Console
- Power Cable
- VGA, PS/2 Cable Kit
- Bracket Kit and Required Hardware
- Quick Installation Guide
- Keys

SINGLE-/DUAL-RAIL LCD CONSOLE WITH INTEGRATED PRO3 KVM

- Rack Console
- 12V DC, 6A External Power Supply
- Bracket Kit and Required Hardware
- Quick Installation Guide
- Keys
- User Manual
- DB9-to-RJ11 Serial Flash Cable

DUAL RAIL PART NUMBER

- F1DC100P-DR
- F1DC101P-DR
- F1DC108B-DR

- F1DC116B-DR

SINGLE RAIL PART NUMBER

- F1DC100P-SR
- F1DC101P-SR
- F1DC108B-SR

- F1DC116B-SR
- F1DC102P-SR

DESCRIPTION

- 15" LCD Rack Console
- 17" LCD Rack Console
- 17" LCD Rack Console with Built-In 8-Port KVM Switch
- 17" LCD Rack Console with Built-In 16-Port KVM Switch
- 19" LCD Rack Console

CABLES** (Not included with integrated KVM)

- F1D9400-06 OmniView Series Dual-Port KVM Cable, PS/2, 6 ft.
- F1D9400-10 OmniView Series Dual-Port KVM Cable, PS/2, 10 ft.
- F1D9400-15 OmniView Series Dual-Port KVM Cable, PS/2, 15 ft.
- F1D9400-25 OmniView Series Dual-Port KVM Cable, PS/2, 25 ft.
- F1D9401-06 OmniView Series Dual-Port KVM Cable, USB, 6 ft.
- F1D9401-12 OmniView Series Dual-Port KVM Cable, USB, 12 ft.
- F1D108-CBL OmniView PRO Series Daisy-Chain Cable, 2 ft.

**One cable is required for every two servers attached to integrated KVM.