

BELKIN®

USB 2.0 and FireWire 6-Port PCI Card

Add 3 Hi-Speed USB 2.0 and 3 FireWire® ports directly to your computer

ENGLISH | USB 2.0 and FireWire 6-Port PCI Card

This PCI Card gives your computer a bandwidth up to 40 times greater than USB 1.1 with three USB 2.0 ports and three FireWire ports. It's the ideal interface for transferring extremely large files from USB 2.0 and FireWire peripherals at ultrafast speeds.

Benefits

- Features 3 USB 2.0 480Mbps ports: 2 external and 1 internal
- Provides 3 FireWire 400Mbps ports: 2 external and 1 internal
- Installs with Plug-and-Play ease
- Offers compatibility with any USB or FireWire peripheral

DEUTSCH | USB 2.0 und FireWire 6-Port PCI-Karte

Mit drei USB-2.0-Anschlüssen und drei FireWire-Anschlüssen ermöglicht diese PCI-Karte Ihrem Computer eine 40-mal so große Bandbreite wie USB 1.1. Dies ist die ideale Schnittstelle zur ultraschnellen Übertragung besonders großer Dateien, die auf USB-2.0- oder FireWire-Geräten gespeichert sind.

Vorzüge

- Drei USB-2.0-Anschlüsse (480 Mbit/s): zwei externe und ein interner
- Drei FireWire-Anschlüsse (400 Mbit/s): zwei externe und ein interner
- Einfache Installation mit Plug-and-Play
- Kompatibel mit allen USB- und FireWire-Peripheriegeräten

ESPAÑOL | Tarjeta PCI USB 2.0 y FireWire de 6 puertos

Esta Tarjeta PCI le proporciona a su ordenador un ancho de banda 40 veces superior a USB 1.1, con tres puertos USB 2.0 y tres puertos FireWire. Es la interfaz ideal para transferir archivos muy grandes desde periféricos USB 2.0 y FireWire a velocidades ultrarrápidas.

Ventajas

- Dispone de 3 puertos USB 2.0 de 480 Mbps: 2 externos y 1 interno
- Proporciona 3 puertos FireWire de 400 Mbps: 2 externos y 1 interno
- Se instala con la comodidad del plug-and-play
- Ofrece compatibilidad con cualquier periférico USB o FireWire

FRANÇAIS | Carte PCI 6 ports USB 2.0 à haut débit et FireWire

Cette Carte PCI procure à votre ordinateur un débit 40 fois plus rapide que l'USB 1.1, en plus de trois ports USB 2.0 et trois ports FireWire. Il s'agit de l'interface idéale pour le transfert de fichiers volumineux depuis des périphériques USB 2.0 et FireWire à un débit ultra-rapide.

Avantages

- Comprend trois ports USB 2.0 de 480 Mbps : 2 externes et 1 interne
- Comprend également trois ports FireWire de 400 Mbps : 2 externes et 1 interne
- Installation conviviale Plug-and-Play
- Compatible avec tous les périphériques USB et FireWire

NEDERLANDS | 6-poorts USB 2.0 FireWire PCI-kaart

Deze PCI-kaart met drie USB 2.0-poorten en drie FireWire-poorten voorziet uw computer van een bandbreedte die 40 keer groter is dan bij USB 1.1. Het is de ideale interface voor de ultrasnelle overdracht van zeer grote bestanden van en naar apparaten met een USB 2.0- of FireWire-aansluiting.

Voordelen

- Voorziet u van drie USB 2.0 480Mbps-poorten: twee externe en één interne
- Voorziet u van drie FireWire 400Mbps-poorten: twee externe en één interne
- Is eenvoudig te installeren dankzij Plug-and-Play
- Is compatibel met alle USB- en FireWire-apparaten

ITALIANO | Scheda PCI USB 2.0 e FireWire a 6 porte

Con questa scheda PCI, il vostro computer disporrà di tre porte USB 2.0 e tre porte FireWire per una larghezza di banda 40 volte più ampia rispetto all'USB 1.1. È l'interfaccia ideale per trasferire file molto pesanti da periferiche USB 2.0 e FireWire a velocità elevatissime.

Vantaggi

- Tre porte USB 2.0 da 480 Mbps: 2 esterne e 1 interna
- Aggiunge 3 porte FireWire® da 400 Mbps: 2 esterne e 1 interna
- Si installa facilmente grazie al plug and play
- Compatibile con qualsiasi periferica USB o FireWire

Package Includes

- USB 2.0 and FireWire 6-Port PCI Card
- 6-Pin to 4-Pin FireWire Cable
- Driver CD with Ulead Software
- User Manual

System Requirements

PC Requirements

- 266MHz Pentium® II processor
- Windows® 98 SE, 2000, Me, or XP
- 32MB RAM
- Available PCI version 2.1 slot

Mac® Requirements

- Mac OS® 9.0 or higher for full-speed USB
- Mac OS X v10.2.8 and above for Hi-Speed USB 2.0 (480Mbps)

Ulead® VideoStudio® 5.0 System Requirements

- Windows 98, 98 SE, 2000, Me, or XP
- 300MHz Pentium II processor (500MHz Pentium III recommended)
- 64MB RAM (128MB recommended)
- 300MB of available hard-disk space (4GB recommended)
- CD or DVD drive
- Mouse or other Windows pointing device

Ulead Photo Express™ My Custom Edition System Requirements

- Windows 95 OSR2, 98, Me, 2000, NT® 4.0 with SP4 or above
- Pentium 166MHz or above processor
- 32MB RAM, 70MB available hard-disk space
- Microsoft® Internet Explorer 5 or above
- True-colour or high-colour display and monitor
- Mouse or pressure-sensitive graphics tablet compatible with WinTab™

Ulead Cool 360™ System Requirements

- Windows 98 or NT® 4.0
- Pentium processor
- 32MB RAM
- 20MB of available hard-disk space
- 800x600 pixels or higher desktop area
- True-colour or high-colour display adapter and monitor
- Windows pointing device

Compliance

- Hi-Speed USB 2.0 specification
- OHCI
- FCC for home and office
- CE emissions and immunity standards
- C-Tick

BELKIN LIFETIME PRODUCT WARRANTY

For the life of the product, Belkin warrants that this device shall be free of defects in design, assembly, material, and workmanship (free replacement or comparable product). See the included warranty for more details.

BELKIN®

www.belkin.com

Belkin Ltd.
+44 (0) 1933 35 2000
Rushden,
United Kingdom

Belkin B.V.
+31 (0) 20 654 7300
Schiphol-Rijk,
Netherlands

Belkin GmbH
+49 (0) 89 143405 0
Munich,
Germany

Belkin SAS
+33 (0) 1 41 03 14 40
Boulogne-Billancourt,
France



F5U508vea1



7 22868 60179 2



Designed in the USA

Made in China

© 2006 Belkin Corporation. All rights reserved. All trade names are registered trademarks of respective manufacturers listed. Mac, Mac OS, the Mac logo, FireWire, and the FireWire logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. Microsoft, Windows, and the Windows logo are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

P47208ea

