

BELKIN®

N1 VISION

WIRELESS MODEM ROUTER

(((N1)))
MIMO



ADSL MODEM integrated

BELKIN

The most advanced interactive network display



WIRELESS COVERAGE

Features:

- Plug-and-play “CD-less” setup
- Easy security setup with support for Wi-Fi Protected Setup™ and multiple SSID
- 3x3 MIMO design for the fastest wireless speed and best wireless coverage
- 802.11n draft 2.0-compliant
- Integrated ADSL 2+ Modem
- Gigabit LAN ports

Belkin's N1 Vision Wireless Router with integrated Modem shows relevant network information on its interactive network display. You can quickly view your network's broadband speed, computer bandwidth usage, and the status of your network devices—all from an easy-to-read display.

Ideal usage: streaming video, music, and photos; online gaming; surfing the Web; chatting with friends; and emailing. For optimal wireless performance, use N1 clients in your network.

Belkin's N1 Vision Wireless Router with integrated Modem is easy to set up with a true Plug-and-Play “CD-less” setup feature and comes with simple network security instructions through the LCD.

Package Includes:

N1 VISION Wireless Router with integrated Modem
 ADSL Filter (if not supplied by local ISP)
 Quick Installation Guide
 CD with User Manual on CD-rom
 Power Supply
 RJ11 Phone Cord
 RJ45 Ethernet Networking Cable
 Registration Card

**Manufacturer's
 Lifetime Warranty***

System Requirements:

Computer running Windows® 2000, XP, or Vista™; or Mac OS® X v10.2, 10.3, 10.4 or 10.5
 At least one computer with an installed network interface card
 TCP/IP networking protocol installed on each computer
 Internet browser
 Minimum 64MB of RAM
 CD-ROM drive

Specifications

Compatible with:

IEEE 802.11g
 IEEE 802.11b
 IEEE 802.11n draft 2.0*

Ports:

ADSL – 1 RJ11 Port
 LAN – 4 Gigabit RJ45 Ports

Security:

Wi-Fi Protected Setup™
 WPA™, WPA2™
 64-/128-bit WEP encryption
 Multiple SSID

VPN Support:

PPTP
 IPsec pass-through

ADSL Protocol Supported

PPPoE (PPP over Ethernet)
 PPPoA (PPP over ATM)
 Dynamic IP (1483 Bridge)
 Static IP (IPoA)

Browser-Based Management

Plug-and-Play Setup

Maximum Users:

253 (LAN)
 16 (WLAN)

Patent-Pending LCD:

- Network Display
 - Download/Upload Speedometer
 - Usage
 - Connected Devices
 - Guest Access Network

Operating Range:

Up to 485m**

Link Rate:

Up to 300Mbps in 20/40MHz Channel Mode

NOTE: The standard transmission rate—300Mbps—is the physical data rate. Actual data throughput will be lower.



Part Number
F5D8632uk4A

Description
N1 Vision Wireless Modem Router

UPC
722868656853

Screens are a representation of Belkin's interactive network display. Actual download and upload speeds will depend on your Internet service provider.

