



Specification:

- 1. Connector Type : ST/PC Multimode
- 2. Connector Type : SC/PC Multimode
- 3. Cable Type :  
Zipcord cable,  $\varnothing 3.0\text{mm}$ , 62.5/125um Multimode,  
Calbe Jacket : Orange color, PVC material
- 4. Length : xM
- 5. Cable Marker
- 6. Shrink Tube

Performance:

- a. Insertion Loss :  $< 0.5 \text{ dB}$
- b. Fiber Extention :  $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- c. Ferrule End-face Radius :  $10 < R < 30\text{mm}$
- d. Apex Offset :  $< 50\mu\text{m}$
- e. Increase in insertion loss after 500 mating :  $0.2 \text{ dB Max.}$
- f. Operation Temperature :  $-20^{\circ}$  to  $+70^{\circ}$
- g. Storage Temperature :  $-40^{\circ}$  to  $+80^{\circ}$
- h. Humidity (non-condensing) 95%RH

**BELKIN®**

BELKIN CORPORATION  
 501 West Walnut Street, Compton, CA 90220-5221, USA  
 TEL: 310-898-1100; FAX: 310-898-1111  
 www.belkin.com

---

PART NO.: A2F20207

---

DES.: ST to SC Duplex patch cord