



### Specification :

1. Connector Type : LC/PC Singlemode.
2. Connector Type : ST/PC Singlemode.
3. Cable Type :  
Zipcord cable,  $\varnothing 3.0\text{mm}$ , 8.3/125um Singlemode.  
Cable Jacket : Yellow color, PVC material.
4. Cable Marker.
5. Shrink Tube.
6. Length : xM.

### Performance :

- a. Insertion Loss :  $< 0.3 \text{ dB}$ .
- b. Return Loss :  $> 40 \text{ dB}$ .
- c. Fiber Extention :  $-0.05\mu\text{m} < H < +0.05\mu\text{m}$ .
- d. Ferrule End-face Radius :  $10 < R < 25\text{mm}$ .
- e. Apex Offset :  $< 50\mu\text{m}$ .
- f. Increase in insertion loss after 500 mating :  $0.2 \text{ dB Max}$ .
- g. Operation Temperature :  $-20^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$ .
- h. Storage Temperature :  $-40^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$ .
- i. Humidity (non-condensing) 95%RH.

# BELKIN®

BELKIN CORPORATION  
501 West Walnut Street, Compton, CA 90220-5221, USA  
TEL: 310-898-1100; FAX: 310-898-1111  
www.belkin.com

PART NO.: F2F802L0

DES.: ST to LC Duplex patch cord