

## Gold Series IEEE 1284 Parallel Printer Cable (A/B) - 1.8M (6 feet) - F2A046b06-GLD

The Gold Series Parallel Printer Cable attaches your IEEE 1284 printer with a Centronics 36-port to your PC with a DB25 port. Featuring 24K gold plated corrosion-proof connectors for maximum conductivity.



©2002 Belkin Corporation

### Product Features:

- Fastest data transfer for maximum performance (up to 10 times faster than non-compliant IEEE 1284 cables).
- Quality assured with the Belkin lifetime warranty.
- 24K gold plated corrosion-proof connectors for maximum conductivity.
- Tactilite®: molded strain relief provides a 360-degree turning radius for true protection against damage to the conductors.
- Flexitec®: cable jacket is very durable and extremely flexible for use in tight areas.
- Oversized ergonomic thumbscrews make installation a breeze.
- 18 tightly woven conductor pairs have each data line paired with a ground line to minimize cross talk, noise and other interference, ensuring error-free printing.
- PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress.
- 28 AWG stranded tinned copper conductors are individually insulated in polypropylene to minimize cross talk, ensuring high-speed, error-free transmission.
- Tactilite®: overmold is a supple polymer designed to increase flexibility while maintaining durability.
- 24K gold plated copper connectors provide maximum conductivity with no data loss.
- Double shielded braid and foil to meet IEEE 1284 specifications, and ensure compliance with FCC requirements, reducing EMI/RFI.
- Ground indents provide excellent conductivity and retention with mating conductors.
- Aluminum undermold shield helps to meet FCC requirements on EMI/RFI interference.

Belkin Ltd  
Rushden  
United Kingdom

Belkin BV  
Schiphol-Rijk  
Netherlands

Belkin GmbH  
Munich  
Germany

Belkin SAS  
Billancourt  
France

Belkin Nordic  
Stockholm  
Sweden