


## Pro Series Non-IEEE Parallel Printer Cable (A/B) - 0.7m - F2A036b0.7M

This Standard Series Bi-Directional Printer Cable attaches any PC with DB25 female parallel ports to parallel printers with Centronics 36 female ports. Supports any non IEEE 1284 compliant computers or printers.



©2008 Belkin Components

### Características del producto:

- Without Retail Packaging
- Aluminum undermold shielding helps to meet FCC requirements on EMI/RFI interference.
- PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress.
- Ground indents provide excellent conductivity and retention with mating conductors.
- 28 AWG stranded tinned copper conductors are individually insulated in polypropylene to minimize cross talk, ensuring high-speed, error-free transmission.
- Molded strain relief and PVC overmolding to ensure a lifetime of error-free data transmission.
- Oversized ergonomic thumbscrews make installation a breeze.
- Gold plated copper contacts provide maximum conductivity and keep data loss to a minimum.
- State-of-the-art-wiring design ensures 100% compatibility with all devices 100% of the time.
- Belkin Lifetime Warranty
- Attaches any PC with DB25 female parallel ports to parallel printers with Centronics 36 female ports

Belkin Ltd  
Rushden  
Reino Unido

Belkin BV  
Schiphol-Rijk  
Países Bajos

Belkin GmbH  
Munich  
Alemania

Belkin SAS  
Billancourt  
Francia

Belkin Nordic  
Stockholm  
Suecia