

External SCSI III Cable - 1.8m(6 feet) - F2N991b06

When John Atanasoff constructed the first semi-electronic digital computing device in 1939 he never could have imagined that over sixty years later, Belkin components would carry every SCSI cable imaginable. The Micro DB68 Male to Micro DB68 Male Pro Series (fast and wide) SCSI III Cable is used to interface any two SCSI devices, such as a scanner and CD-ROM drive, when each has Micro DB68 female ports.



©2000 Belkin Components

Características del producto:

- Rated for SCSI III applications.
- Double shielded (braid and foil) to meet SCSI specifications and ensure compliance with FCC requirements reducing EMI/RFI interference.
- Low-capacitance impedance matched 28 AWG stranded tinned copper are individually insulated in polypropylene.
- The Belkin Lifetime Warranty.
- 25 or 34 tightly woven conductor pairs ensures that each data line is paired with a ground line to minimize interference ensuring error-free data transmissions.
- State-of-the-art wiring design ensures 100% compatibility.
- Gold plated copper contacts for a clean, clear transmission.
- PVC premold encapsulates individual conductors to eliminate stress.
- Flexitec®#153: PVC rubberized cable jacket is extremely flexible for use in tight areas.
- Aluminum undermold shield helps meet FCC requirements.
- Ground indents provide excellent conductivity and retention with mating connector.
- Without Retail Packaging

Belkin Ltd
Rushden
Reino Unido

Belkin BV
Schiphol-Rijk
Países Bajos

Belkin GmbH
Munich
Alemania

Belkin SAS
Billancourt
Francia

Belkin Nordic
Stockholm
Suecia