

## External SCSI III Adapter Cable - 1.2m(4 foot) - F2N1035-04

The Micro DB68 Male to DB25 Male Pro Series (fast and wide) SCSI III Cable. Used to interface any two SCSI devices such as storage devices, wherein one has a Micro DB68 female port and the other has a DB25 female port.



©2000 Belkin Components

### Características del producto:

- Rated for SCSI III applications.
- Double shielded (braid and foil) to meet SCSI specifications and ensure compliance with FCC requirements reducing EMI/RFI interference.
- Low-capacitance impedance matched 28 AWG stranded tinned copper are individually insulated in polypropylene.
- Full lifetime warranty.
- 25 or 34 tightly woven conductor pairs ensures each data line is paired with a ground line to minimize interference ensuring error-free data transmissions.
- State-of-the-art wiring design ensures 100% compatibility.
- Gold plated copper contacts for a clean clear transmission.
- PVC premold encapsulates individual conductors to eliminate stress.
- Flextech®153: PVC rubberized cable jacket is extremely flexible for use in tight areas.
- Aluminum undermold shield helps meet FCC requirements.
- Ground indents provide excellent conductivity and retention with mating connector.

Belkin Ltd  
Rushden  
Reino Unido

Belkin BV  
Schiphol-Rijk  
Países Bajos

Belkin GmbH  
Munich  
Alemania

Belkin SAS  
Billancourt  
Francia

Belkin Nordic  
Stockholm  
Suecia