

## External SCSI II Cable - 1.8m(6 feet) - F2N992-06

The Micro DB50 Male to DB25 Male Pro Serie



©2005 Belkin Components

### Características del producto:

- Rated for SCSI II applications.
- Double shielded (braid and foil) to meet SCSI specifications and ensure compliance with FCC requirements reducing EMI/RFI interference.
- Low-capacitance impedance matched 28 AWG stranded tinned copper are individually insulated in polypropylene.
- The Belkin full lifetime warranty.
- 25 or 34 tightly woven conductor pairs ensures that each data line is paired with a ground line to minimize interference ensuring error-free data transmissions.
- State-of-the-art wiring design ensures 100% compatibility.
- Gold plated copper contacts for a clean, clear transmission.
- PVC pre-mold encapsulates individual conductors to eliminate stress.
- Flex-tec® #153: PVC rubberized cable jacket is extremely flexible for use in tight areas.
- Aluminum undermold shield helps meet FCC requirements.
- Ground indents provide excellent conductivity and retention with mating connector.

Belkin Ltd  
Rushden  
Reino Unido

Belkin BV  
Schiphol-Rijk  
Países Bajos

Belkin GmbH  
Munich  
Alemania

Belkin SAS  
Billancourt  
Francia

Belkin Nordic  
Stockholm  
Suecia