



DB9P

DB9P

PIN OUT

DB9P DB9P

1 \_\_\_\_\_ 1  
 2 \_\_\_\_\_ 2  
 3 \_\_\_\_\_ 3  
 4 \_\_\_\_\_ 4  
 5 \_\_\_\_\_ 5  
 6 \_\_\_\_\_ 6  
 7 \_\_\_\_\_ 7  
 8 \_\_\_\_\_ 8  
 9 \_\_\_\_\_ 9

SHELL \_\_\_\_\_ SHELL

NOTE:

- 1.CABLE:26AWG UL1061 40mm JUMP WIRE.
- 2.D-SUB 9 PIN MALE(DB9P):SOLDER TYPE,GOLD FLASH CONTACTS, BLACK PBT INSULATOR,TIN PLATED SHELL.
- 3.MOLDED TOOLING NUMBER:M  $\frac{1}{2}$  -A09-20x,BIG SIDE MOLDED LOGO: " **BELKIN** ";SMALL SIDE MOLDED P/N LOGO: " **BELKIN** ".
- 4.SHIELD:WITH AL-FOIL SHIELD.
- 5.THUMBSCREW:4\*11.5mm(#4-40UNC) SCREW+ T-WASHER+HEX NUT:4.75\*6mm(#4-40UNC).
- 6.HOOD:MOLDED PVC SMOKE GREY V297 45P

REV	ECN NO.	DESCRIPTION	APPD	DATE

<b>BELKIN</b>		BELKIN COMPONENTS	
TOLERANCE:	APPROVED BY:	BELKIN P/N:	
X. ±	Mars	CC3016aed	
.X ±	CHECKED BY:	CUSTOMER P/N:	
.XX ±	Dong	J00032864	
.XXX ±	DRAWN BY:	DESCRIPTION:	
ANGLE:	Dian		
X' ±	DATE:	DWG. NO.:	
.X' ±	07.10.26		
	SCALE:	UNIT:MM	SHEET: 1 OF 1 REV:00