



Home Series UPS-USB

Model		F6H350-USB	F6H500-USB	F6H650-USB
Input	Capacity	350	500	650
	Max Load	190 W	300 W	360 W
	Voltage Range	105 ~ 135 Vac		
	Frequency	60Hz ±1Hz		
Output	Voltage (On battery)	Simulated Sine Wave, 120Vac ±10%		
	Frequency (On battery)	60Hz ±1Hz		
	Voltage Regulation (AVR)	No AVR		
	Transfer Time	N/A		
Protection and Filtering	Spike Protection	510 Joules		
	EMI/RFI Filter	Meets FCC Class B		
	Overload Protection	UPS Low voltage switch to high voltage switch to battery: 105 ~ 135 ±3 Vac		
	Unit Input	Breaker for overload and short circuit protection		
	Telecommunication Protection	1 In, 2 Out Single Line (2 Wire, RJ11) jacks		
	Short Circuit	UPS shuts down		
Battery	Voltage / Amps	12V / 5Ah	12V / 5Ah	12V / 7Ah
	Type	Sealed, maintenance free lead acid		
	Typical Recharge Time	<8 Hours		
	Protection	Automatic self discharge protection, replace battery indicator LED		
	Battery Run Time	Upto 15 minutes	Upto 28 minutes	Upto 35 minutes
Alarm	Battery Backup	Flashing Red LED and Audible Alarm 10 second continuous		
	Battery Low			
	Overload			
	Fault	Solid Red LED Light		
	Battery Test	Slow beeping sound (about 15 second intervals)		
Communication Port		USB Port		
Environment	Ambient Operation	0 ~ 85% Relative Humidity (Non-condensing); 0 ~ 35° C Operation Temperature		
	Audible Noise	<40dBA at 1 meter		
Physical	Weight (lbs)	8.81	10.14	12.34
	Dimension W x D x H	9.84" x 6.61" x 3.15"		
Compliance		UL/cUL, EMI, IEC 1000-4-2 Level 3, IEC 1000-4-4 Level 2, IEC 1000-4-5 Level 3, FCC Part 68, CS-03, USB models are Microsoft XP Certified.		
Front Panel Switch	AC Power On	Press and hold longer than 2 sec.		
	Power Off	Press and hold longer than 2 sec.		
	Cold Start (Turns DC Power On)	Press and hold longer than 2 sec.		
	Buzzer Silence (On Battery Mode)	Press less than 1.5 sec.		